Model Number 137B23B		ICP ®	PRESSURE	SENSOR
Performance	ENGLISH	SI		
Measurement Range(for ±5V output)	50 psi	345 kPa		Optional versions
Useful Overrange(for ± 10V output)	100 psi	690 kPa	[1]	
Sensitivity(± 15 %)	100 mV/psi	14.5 mV/kPa		
Maximum Pressure	1,000 psi	6,895 kPa		
Resolution	0.01 psi	0.069 kPa	[2]	
Resonant Frequency	≥ 400 kHz	≥ 400 kHz		
Rise Time(Incident)	≤ 6.5 µ sec	≤ 6.5 µ sec		
Non-Linearity	≤ 1.0 % FS	≤ 1.0 % FS	[3]	
Environmental				
Temperature Range(Operating)	-100 to +275 °F	-73 to +135 ℃		
Temperature Coefficient of Sensitivity	≤ 0.05 %/°F	≤ 0.090 %/°C		
Electrical				
Discharge Time Constant(at room temp)	≥ 0.2 sec	≥ 0.2 sec		
Excitation Voltage	22 to 30 VDC	22 to 30 VDC		
Constant Current Excitation	2 to 20 mA	2 to 20 mA		
Output Impedance	≤ 100 Ohm	≤ 100 Ohm		
Output Bias Voltage	8 to 15 VDC	8 to 15 VDC		
Physical				
Sensing Geometry	Compression	Compression		
Sensing Element	Quartz	Quartz		
Housing Material	Aluminum	Aluminum		
Diaphragm	Invar	Invar		
Sealing	Ероху	Ероху		
Electrical Connector	BNC Jack	BNC Jack		
Weight	12.4 oz	352 gm	[2]	

OPTIONAL VERSIONS

Revision: E

ECN #: 55416

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

[1] For +10 volt output, minimum 26 VDC supply voltage required. Negative 10 volt output may be limited by output bias.

[2]Typical.

[3]Zero-based, least-squares, straight line method.
[4]See PCB Declaration of Conformance PS023 for details.

SUPPLIED ACCESSORIES:

Model PCS-1 Calibration of dynamic pressure sensors up to 100% range

Entered: ND Engineer: RPF Sales: MV Approved: RPF Spec Number: Date: 12/14/2024 Date: 12/14/2024 Date: 12/14/2024 Date: 12/14/2024 46932



3425 Walden Avenue, Depew, NY 14043

All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice. ICP® is a registered trademark of PCB Piezotronics, Inc.

CE UK