

	ENGLISH	SI
Performance		
Channels	24	24
Environmental		
Enclosure Rating	Nema 4X	IP66
Physical		
Electrical Connector(Output, Vibration)	BNC Jack	BNC Jack
Electrical Connector(Output, Temperature)	BNC Jack	BNC Jack
Electrical Connector(Output, Vibration)	2-Pin Mil	2-Pin Mil
Electrical Connector(Input)	Terminal Block	Terminal Block
Electrical Connector(Output, Vibration)	Terminal Block	Terminal Block
Housing Material	Fiberglass	Fiberglass
Size (Height x Width x Depth)	20.6 in x 16.6 in x 7.9 in	523.2 mm x 421.6 mm x 200.6 mm
Weight	24.1 lb	10.9 kg

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

691026 - 2 Conduit Fittings, 1.5 Inch

691040 - 24 Individual Cord Grips, PGME07

691044 - 2 Individual Cord Grips, PGME21

691048 - 24 Individual cord grips, PGME07 and 2 individual cord grips, PGME21

691060 - 48 Individual Cord Grips, PGME07


691064 - 4 Individual Cord Grips, PGME21

691065 - 4 Conduit Fittings, 1.5 Inch.

NOTES:
[1]See PCB Declaration of Conformance PS174 for details.

SUPPLIED ACCESSORIES:
Model 080A192 4-socket terminal block (2)

Entered: LK	Engineer: gs	Sales: MC	Approved: BAM	Spec Number:
Date: 08/26/2020	Date: 08/26/2020	Date: 08/26/2020	Date: 08/26/2020	70849



IMI SENSORS
A PCB PIEZOTRONICS DIV.

3425 Walden Avenue, Depew, NY 14043

Phone: 800-959-4464
Fax: 716-684-3823
E-Mail: imi@pcb.com



All specifications are at room temperature unless otherwise specified.
In the interest of constant product improvement, we reserve the right to change specifications without notice.
ICP® is a registered trademark of PCB Piezotronics, Inc.