Model Number BC	BC - 2 SOCKET MIL MS3106 HIGH TEMPERATURE						ision: A I #: 48437
Performance Connector Style Connection Type Coupling Method Coupling Thread Strain Relief Environmental	ENGLISH MIL-C-5015 Multi-conductor 2-socket Threaded 5/8-24 female Potted	SI MIL-C-5015 Multi-conductor 2-socket Threaded 5/8-24 female Potted	OPTIONAL VERSIONS Optional versions have identical specifications and accessories as lie except where noted below. More than one option materials are supplied to the control of the contr				
Temperature Range Physical	-65 to +325 °F	-55 to +163 °C	Entered: LK	Engineer: KW	Sales: DAM	Approved: BAM	Spec Number:
ROHS Compliant Size (OD x Length) Weight	Yes 0.87 in x 1.4 in 0.49 oz	Yes 22 mm x 36 mm 14 gm		Date: 11/19/2018	 	Date: 11/19/2018	32619
All specifications are at room temper	rature unless otherwise specified. provement, we reserve the right to change	Č	A PCB PIEZ	ENSORS OTRONICS DIV.	IMI Sensors 3425 Walde Depew, NY UNITED ST Phone: 800 Fax: 716-68	n 14043 ATES -959-4464 4-3823	

E-Mail: imi@pcb.com Web site: http://www.imi-sensors.com