Model Number PA	CABLE CONNECTOR						ision: NR I #: 42594
Performance Connector Style Connection Type Coupling Method Coupling Thread Strain Relief Environmental Temperature Range	ENGLISH MIL-C-5015 2-socket Jack (female socket / recepticle) Threaded 5/8-24 female Molded Boot -67 to +356 °F	SI MIL-C-5015 2-socket Jack (female socket / recepticle) Threaded 5/8-24 female Molded Boot -55 to +180 °C	OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.				
Physical Size (OD x Length x Height)	.75 in x 1.63 in x 1.5 in	19.1 mm x 41.4 mm x 38.1 mm	Entered: AP	Engineer: jg	Sales: HJB	Approved: BAM	Spec Number:
Weight	0.65 oz	18.4 gm	Date: 2/26/2014	Date: 2/26/2014	Date: 2/26/2014	Date: 2/26/2014	58212
	nperature unless otherwise specified. t improvement, we reserve the right to cha	ange specifications without notice.	c		_11	Ш	<u>u</u>
$ICP^{\textcircled{B}}$ is a registered trademark of PCB Group, Inc.			PCB PIEZOTRONICS ^{**} 3425 Walden Avenue, Depew, NY 14043			Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com	