


| Model Number RZ | CABLE CONNECTOR | | Revision: A ECN #: 51333 | |
|--|---|--|--|--------------|
| Performance Connector Style Connection Type Strain Relief Environmental Temperature Range Maximum Shock Vibration Survivability Physical Electrical Connections(Pin 1) Electrical Connections(Pin 2) Electrical Connections(Pin 3) Electrical Connections(Pin 4) Electrical Connections(Pin 5) Electrical Connections(Pin 6) Electrical Connections(Pin 7) Electrical Connections(Shell) Electrical Connections(Shell) ROHS Compliant Housing Material Size (OD x Length) | ENGLISH LEMO FGG.1B.307 7-pin Molded Boot -40 to 176 °F 100 g pk 15 g pk Pos (+) Power No Connection Shield Neg (-) Signal Pos (+) Signal Negative (-) Power No Connection Shield Ground Yes Chrome-Plated Brass 0.47 in x 1.65 in | SI LEMO FGG.1B.307 7-pin Molded Boot -40 to 80 °C 981 m/s ² pk 147 m/s ² pk Pos (+) Power No Connection Shield Neg (-) Signal Pos (+) Signal Negative (-) Power No Connection Shield Ground Yes Chrome-Plated Brass 12 mm x 42 mm | OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used. | |
| NOTES: | | | | |
| | | | | |
| Entered: LK | Engineer: GD | Sales: KK | Approved: BAM | Spec Number: |
| Date: 12/09/2020 | Date: 12/09/2020 | Date: 12/09/2020 | Date: 12/09/2020 | 72913 |
|  Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com 3425 Walden Avenue, Depew, NY 14043 | | | | |
| All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice. | | | | |