


Model Number SC	CABLE CONNECTOR			Revision: NR ECN #: 50640
Performance Connector Style Connection Type Connection Type Coupling Method Environmental Temperature Range Radiation Exposure Limit(Integrated Neutron Flux) Radiation Exposure Limit(Integrated Gamma Flux) Physical Size (OD x Length) Weight Sealing	ENGLISH Multi-conductor 2-pin Plug (male pin) Threaded -76 to 500 °F 1 E10 N/cm ² 1 E8 rad 0.51 in x 1.16 in 0.42 oz Hermetic	SI Multi-conductor 2-pin Plug (male pin) Threaded -60 to 260 °C 1 E10 N/cm ² 1 E8 rad 13 mm x 29.5 mm 11.9 gm Hermetic		OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.
				NOTES: [1]When used with braided hardline cable
	Entered: LK	Engineer: EB	Sales: MC	Approved: RPF
	Date: 04/09/2020	Date: 04/09/2020	Date: 04/09/2020	Date: 04/09/2020 73014
All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.				Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com 3425 Walden Avenue, Depew, NY 14043